

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 08/19/2014 : Version:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : MASTER CHAIN LUBE 10 OZ.

Product code : CL16

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Chain and Cable Lube

1.3. Details of the supplier of the safety data sheet

Master Chemical 4635 Willow Drive Medina, MN 55340 - USA T: 612-478-2360

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Aerosol 1 H222 Compressed gas H280 Muta. 1B H340 Carc. 1A H350

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



 \Diamond



GHS02

GHS04

GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H222 - Extremely flammable aerosol

H280 - Contains gas under pressure; may explode if heated

H340 - May cause genetic defects

H350 - May cause cancer

Precautionary statements (GHS-US) : P201 - Obtain special instructions

P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking

P211 - Do not spray on an open flame or other ignition source P251 - Pressurized container: Do not pierce or burn, even after use

P280 - Wear protective gloves, protective clothing, eye protection, face protection

P308+P313 - If exposed or concerned: Get medical advice/attention

P405 - Store locked up

P410+P403 - Protect from sunlight. Store in a well-ventilated place

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 $^{\circ}$ C/122 $^{\circ}$ F P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with

local, regional, national, international regulations.

2.3. Other hazards

Other hazards not contributing to the

classification

: Contains gas under pressure; may explode if heated.

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

20/08/2014 EN (English US) 1/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Name | Product identifier | % | Classification (GHS-US) |
|--|---------------------|---------|---|
| distillates (petroleum), hydrotreated heavy naphthenic | (CAS No) 64742-52-5 | 50 - 70 | Acute Tox. 4 (Inhalation:dust,mist), H332 |
| Petroleum gases, liquefied, sweetened | (CAS No) 68476-86-8 | 10 - 30 | Flam. Gas 1, H220 Flam. Liq. 1, H224 Muta. 1B, H340 Carc. 1A, H350 |
| Distillates (Petroleum), hydrotreated light | (CAS No) 64742-47-8 | 10 - 30 | Asp. Tox. 1, H304 |

SECTION 4: First aid measures

Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice

(show the label where possible).

Cough. Assure fresh air breathing. Allow the victim to rest. First-aid measures after inhalation

First-aid measures after skin contact Remove affected clothing and wash all exposed skin area with mild soap and water, followed by

warm water rinse.

Direct contact with the eyes is likely to be irritating. Rinse immediately with plenty of water. First-aid measures after eye contact

Obtain medical attention if pain, blinking or redness persist.

First-aid measures after ingestion Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : May cause genetic defects.

Symptoms/injuries after inhalation : Shortness of breath. May cause cancer by inhalation.

Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

Extinguishing media

: Foam. Dry powder. Carbon dioxide. Water spray. Sand. Suitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns

and injuries.

Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire

reaches explosives. Evacuate area.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information Aerosol level 3.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures Remove ignition sources. No naked lights. No smoking. Isolate from fire, if possible, without

unnecessary risk. Use special care to avoid static electric charges.

For non-emergency personnel 6.1.1.

Protective equipment : Gloves. Safety glasses.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Methods and material for containment and cleaning up 6.3.

: Dam up the liquid spill. For containment

Methods for cleaning up : Store away from other materials.

Reference to other sections

See Heading 8. Exposure controls and personal protection.

20/08/2014 EN (English US) 2/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn,

even after use.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Obtain special instructions. Do not handle until all safety precautions have been read and understood. Eliminate all ignition

sources if safe to do so.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container

closed when not in use. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in

fireproof place.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

Storage area : Store in a well-ventilated place.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5) | | |
|---|-------------------|----------------------------|
| USA ACGIH | ACGIH TWA (mg/m³) | 5 mg/m³ Inhalable fraction |

| Distillates (Petroleum), hydrotreated light (64742-47-8) | | |
|--|-----------------|-----------------|
| USA ACGIH | ACGIH TWA (ppm) | 200 ppm 8 Hours |

| Petroleum gases, liquefied, sweetened (68476-86-8) USA ACGIH ACGIH TWA (ppm) 1000 ppm Listed under Aliphatic hydrocarbon gases alkane C1-C4 | | |
|--|------------------------|------------|
| | | , , , |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 1800 mg/m³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm |

8.2. Exposure controls

Appropriate engineering controls : Local exhaust venilation, vent hoods.

Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.





Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses. Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear appropriate mask.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas
Appearance : Liquid.

Color : Colourless to yellow.
Odor : Characteristic. Mild.
Odor threshold : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : No data available

20/08/2014 EN (English US) 3/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Freezing point : No data available

Boiling point : -31.1 °C (Lowest Component)
Flash point : -96.23 °C (Lowest Component)

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : No data available
Relative vapor density at 20 °C : No data available

Relative density : 0.88

Solubility : Insoluble in water. : No data available Log Pow Log Kow : No data available : No data available Viscosity, kinematic Viscosity, dynamic : No data available : No data available Explosive properties Oxidizing properties : No data available Explosive limits : No data available

9.2. Other information

VOC content : 22.5 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5) | |
|---|--------------|
| LD50 oral rat | > 5000 ml/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat (mg/l) | 2.18 mg/l/4h |

| Distillates (Petroleum), hydrotreated light (64742-47-8) | |
|--|--|
| LD50 oral rat | > 5000 mg/kg body weight |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat (mg/l) | > 5.28 mg/l/4h Based on lack of mortality and systemic effects |

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : May cause genetic defects.

Carcinogenicity : May cause cancer.

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

20/08/2014 EN (English US) 4/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation : Shortness of breath. May cause cancer by inhalation.

SECTION 12: Ecological information

12.1. Toxicity

| distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5) | | |
|---|----------------|----------------------|
| | EC50 Daphnia 1 | > 1000 mg/l 48 HOURS |

12.2. Persistence and degradability

MASTER CHAIN LUBE 10 OZ.

Persistence and degradability Not established.

distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

Persistence and degradability Not established.

Distillates (Petroleum), hydrotreated light (64742-47-8)

Persistence and degradability Not established.

Petroleum gases, liquefied, sweetened (68476-86-8)

Persistence and degradability Not established.

12.3. Bioaccumulative potential

MASTER CHAIN LUBE 10 OZ.

Bioaccumulative potential Not established.

distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

Bioaccumulative potential Not established.

Distillates (Petroleum), hydrotreated light (64742-47-8)

Bioaccumulative potential Not established.

Petroleum gases, liquefied, sweetened (68476-86-8)

Bioaccumulative potential Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under

pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste

disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Flammable vapors may accumulate in the container.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN1950, Aerosols, 2.1, Limited Quantity ICAO/IATA (air): UN1950, Aerosols, 2.1, Limited Quantity IMO/IMDG (water): UN1950, Aerosols, 2.1, Limited Quantity

Special Provisions: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

14.2. UN proper shipping name

DOT Proper Shipping Name : Aerosols

flammable, (each not exceeding 1 L capacity)
: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Department of Transportation (DOT) Hazard

Classes

20/08/2014 EN (English US) 5/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Packaging Non Bulk (49 CFR 173.xxx) : None

DOT Packaging Bulk (49 CFR 173.xxx) : None

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 75 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

| MASTER CHAIN LUBE 10 OZ. | |
|-------------------------------------|---|
| SARA Section 311/312 Hazard Classes | Fire hazard Immediate (acute) health hazard Sudden release of pressure hazard |

distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 311/312 Hazard Classes Immediate (acute) health hazard

Distillates (Petroleum), hydrotreated light (64742-47-8)

SARA Section 311/312 Hazard Classes Immediate (acute) health hazard

Petroleum gases, liquefied, sweetened (68476-86-8)

| retroteum guses, inqueneu, sweeteneu (vo+re vo v) | |
|---|-----------------------------------|
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard |
| | Fire hazard |
| | Sudden release of pressure hazard |

15.2. International regulations

CANADA

| MASTER CHAIN LUBE 10 OZ. | |
|--------------------------|--|
| WHMIS Classification | Class B Division 5 - Flammable Aerosol |

distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

Listed on the Canadian DSL (Domestic Sustances List)

Distillates (Petroleum), hydrotreated light (64742-47-8)

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

EU-Regulations

distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

20/08/2014 EN (English US) 6/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification according to Directive 67/548/EEC or 1999/45/EC

Carc.Cat.1; R45 Muta.Cat.2; R46

F+; R12

Full text of R-phrases: see section 16

15.2.2. National regulations

distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

Listed on AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

15.3. US State regulations

No additional information available

SECTION 16: Other information

Other information : None.

Full text of H-phrases: see section 16:

| Acute Tox. 4 (Inhalation:dust,mist) | Acute toxicity (inhalation:dust,mist) Category 4 |
|-------------------------------------|--|
| Asp. Tox. 1 | Aspiration hazard Category 1 |
| Carc. 1A | Carcinogenicity Category 1A |
| Compressed gas | Gases under pressure Compressed gas |
| Flam. Aerosol 1 | Flammable aerosol Category 1 |
| Flam. Gas 1 | Flammable gases Category 1 |
| Flam. Liq. 1 | Flammable liquids Category 1 |
| Muta. 1B | Germ cell mutagenicity Category 1B |
| H220 | Extremely flammable gas |
| H222 | Extremely flammable aerosol |
| H224 | Extremely flammable liquid and vapor |
| H280 | Contains gas under pressure; may explode if heated |
| H304 | May be fatal if swallowed and enters airways |
| H332 | Harmful if inhaled |
| H340 | May cause genetic defects |
| H350 | May cause cancer |

NFPA health hazard : 2 - Intense or continued exposure could cause temporary

incapacitation or possible residual injury unless prompt

medical attention is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all

ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard
Physical : 1 Slight Hazard
Personal Protection : B

SDS US (GHS HazCom 2012)

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

20/08/2014 EN (English US) 7/7