



# SAFETY DATA SHEET

## SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

<b>Product ID:</b>	MSCC350	<b>Date Printed:</b>	Jun 06, 2022
<b>Product Name:</b>	Motospray Contact Cleaner, 350gm	<b>Supersedes Date:</b>	N/A
<b>Revision Date:</b>	Jun 06, 2022		
<b>Version:</b>	1.0		
<b>Manufacturer's Name:</b>	MMP Industrial Pty Ltd		MMP Industrial New Zealand
<b>Address:</b>	3-5 Hannabus Place Mulgrave, AU, NSW, 2756		21 Highbrook Drive, East Tamaki, Manukau Auckland New Zealand
<b>Emergency Phone:</b>	13 11 26		0800 764 766
<b>Information Phone Number:</b>	612 4577-6977		649 250-4635
<b>Fax:</b>	612 4577-6969		
<b>Product/Recommended Uses:</b>	Cleaner for electrical circuit boards		

## SECTION 2) HAZARDS IDENTIFICATION

### Classification

Aerosols Category 1  
 Aspiration Hazard - Category 1  
 Skin Irritation - Category 2

### Pictograms



### Signal Word

Danger

### Poisons Schedule

Not applicable

### Hazardous Statements - Health

H304 - May be fatal if swallowed and enters airways  
 H315 - Causes skin irritation

### Hazardous Statements - Physical

H222 - Extremely flammable aerosol  
 H229 - Pressurised container: May burst if heated

### Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.  
 P102 - Keep out of reach of children.  
 P103 - Read label before use.

### Precautionary Statements - Prevention

P241 - Use explosion-proof electrical, ventilating, lighting and all other equipment.  
 P264 - Wash hands, face and exposed skin thoroughly after handling.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

### Precautionary Statements - Response

P312 - Call a POISON CENTER/doctor/physician if you feel unwell.

P321 - Specific treatment- see First Aid on this label.

P378 - Use dry chemical, foam, carbon dioxide to extinguish.

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 - Do NOT induce vomiting.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

P362 + P364 - Take off contaminated clothing. And wash it before reuse.

### Precautionary Statements - Storage

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P405 - Store locked up.

### Precautionary Statements - Disposal

P501 - Dispose of contents/container in accordance with local, regional, national and international regulations.

## SECTION 3) COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0000074-98-6	PROPANE	10% - 30%
0000106-97-8	BUTANE	10% - 30%
0000110-54-3	HEXANE	20% - 100%
0000064-17-5	ETHYL ALCOHOL	1% - 10%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

## SECTION 4) FIRST-AID MEASURES

### Inhalation

Eliminate all ignition sources if safe to do so. Remove source of exposure or move person to fresh air, keep comfortable for breathing and keep warm. If you feel unwell/if concerned: Get medical advice/attention.

### Eye Contact

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention. Take care not to rinse contaminated water into the unaffected eye or onto the face.

### Skin Contact

Take off immediately all contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Avoid direct contact. Wear chemical protective clothing, if necessary. Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. Wash contaminated clothing before re-use or discard. If skin irritation occurs: Get medical advice/attention.

### Ingestion

Rinse mouth. Never give anything by mouth to an unconscious or convulsing person. Give a glass of water to drink. Do NOT induce vomiting. If vomiting occurs naturally, give further water. Immediately call a POISON CENTER/doctor. If vomiting occurs give further water. Get to a doctor or hospital quickly.

### Most Important Symptoms and Effects, Both acute and Delayed

No data available.

### Indication of Any Immediate Medical Attention and Special Treatment Needed

Treat symptomatically.

PPE for First Aiders: Wear overalls, safety glasses and impervious gloves. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other

protective equipment before storing or re-using.

If poisoning occurs, contact a Doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

## SECTION 5) FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Use caution when applying carbon dioxide in confined spaces. Small Fire: Dry chemical, foam, carbon dioxide, water-spray or alcohol-resistant foam. Carbon dioxide can displace oxygen. Large Fire: Water spray, fog or alcohol-resistant foam. For Chlorosilanes: Do not use water; use AFFF alcohol-resistant medium-expansion foam.

### Unsuitable Extinguishing Media

Do not use straight stream of water.

### Specific Hazards in Case of Fire

Flammable gas. Ruptured cylinders may rocket. Vapors may travel to source of ignition and flash back. May form an ignitable vapor/air mixture in closed tanks or containers. Runoff may create fire or explosion hazard. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. May form flammable vapour mixtures with air. Cylinders exposed to fire may vent and release toxic gas through pressure relief devices. On burning or decomposing may emit toxic fumes. Electrical requirements for work area should be assessed according to AS3000. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

### Fire-fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Cool containers with flooding quantities of water until well after fire is out. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Do not allow contaminated extinguishing water to enter the soil, ground-water or surface waters. Damaged cylinders should be handled only by specialists. Large Fire: Dike fire-control water for later disposal; do not scatter the material. Heating can cause expansion or decomposition leading to violent rupture of containers. Use shielding to protect against bursting containers. Stop the flow of gas and use water spray to disperse vapors. Large Fire: Damaged cylinders should be handled only by specialists.

### Special Protective Actions

Wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear. Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

## SECTION 6) ACCIDENTAL RELEASE MEASURES

### Emergency Procedure

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Evacuate and isolate hazard area and keep unauthorized personnel away. Do not walk through released material. Stay upwind of release. Ventilate closed spaces before entering. A vapor-suppressing foam may be used to reduce vapors.

### Recommended Equipment

Wear chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA).

### Personal Precautions

DO NOT breathe gas, vapor or mist.

DO NOT get on skin, eyes or clothing.

Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

### Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Suppress aerosol with water spray jet. Neutralization may be required before discharging sewage into treatment plants. Dike far ahead of liquid spill for later disposal.

### Methods and Materials for Containment and Cleaning up

Rinse away with water. Clean up immediately. Ventilate area after clean-up is complete. Use clean, non-sparking tools to collect absorbed material.

For small spills: wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

For large spills: absorb with vermiculite, dry sand, earth, or similar inert material and deposit in sealed containers for disposal.

## SECTION 7) HANDLING AND STORAGE

### General

Remove contaminated clothing and protective equipment before entering eating areas. Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors, mists or aerosols. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. This product is not intended for human or animal consumption. Eyewash stations and showers should be available in areas where this material is used and stored.

### Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source. Report ventilation failures immediately.

### Storage Room Requirements

Provide secondary containment for toxic materials. Store gas cylinders separately, away from processing and handling areas, and from incompatible materials. Eliminate all sources of ignition. Protect containers against banging or other physical damage when storing, transferring, or using them. Keep containers securely sealed when not in use, check regularly for leaks. Store at temperatures above their respective freezing/melting point, do not expose to temperatures exceeding 50 °C/122 °F. Empty containers retain residue and may be dangerous. Store in dry, well-ventilated, cool areas, out of direct sunlight and away from incompatible materials and other sources of heat. Never use plastic or glass containers for storing flammable liquids. Check regularly for leaks. This material is classified as a Dangerous Good Class 2.1 Flammable Gas as per the criteria of the Australian Dangerous Goods Code and must be stored in accordance with the relevant regulations.

## SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

### Eye protection

Wear safety glasses with side shields.

### Skin Protection

Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Wear a Face Shield. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment.

### Respiratory protection

If risk of inhalation of exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

### Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Natural ventilation should be adequate under normal use conditions.

Chemical Name	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)	ACGIH TWA (ppm)	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	WES TWA (mg/m3)
BUTANE		1000 (EX)				CNS impair		1900
ETHYL ALCOHOL		1000			A3	URT irr	A3	1880
HEXANE				50		CNS impair; peripheral neuropathy; eye irr	Skin; BEI	72
METHANOL		250		200		Headache; eye dam; dizziness; nausea	Skin; BEI	262
PROPANE		Simple asphyxiant (D), explosion hazard (EX)				Asphyxia		

Chemical Name	WES STEL (ppm)	WES STEL (mg/m3)	WES TWA (ppm)	WES HEALTH	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)
BUTANE			800					
ETHYL ALCOHOL			1000		1000	1900		
HEXANE			20		500	1800		
METHANOL	250	328	200	Sk	200	260		
PROPANE					1000	1800		

(C) - Ceiling limit, A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans, BEI - Substances for which there is a Biological Exposure Index or Indices, CNS - Central nervous system, dam - Damage, impair - Impairment, irr - Irritation, URT - Upper respiratory tract

## SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

### Physical and Chemical Properties

Density	8.01 lb/gal
Specific Gravity	0.69
% VOC	92.32%
Density VOC	7.40 lb/gal
% Solids By Weight	0.00%

---

Appearance	Colourless liquid
Odor Description	Characteristic of paint thinners
Odor Threshold	Data not available
pH	Data not available
Water Solubility	Insoluble in water
VOC Part A & B Combined	Data not available
Flash Point Symbol	>
Flash Point	1 °C
Viscosity	Data not available
Lower Explosion Level	Data not available
Vapor Pressure	Data not available
Upper Explosion Level	Data not available
Vapor Density	Data not available
Freezing Point	Data not available
Melting Point	Data not available
Low Boiling Point	Data not available
High Boiling Point	Data not available
Auto Ignition Temp	Data not available
Decomposition Pt	Data not available
Evaporation Rate	Data not available
Coefficient Water/Oil	Data not available

## SECTION 10) STABILITY AND REACTIVITY

### Stability

The product is stable under normal storage conditions.

### Conditions to Avoid

Avoid heat, sparks, flame, elevated temperatures, sources of ignition and contact with incompatible materials. Elevated temperatures and sources of ignition.

### Hazardous Reactions/Polymerization

Will not occur.

### Incompatible materials

Oxidizing agents.

### Hazardous Decomposition Products

Oxides of carbon and nitrogen, smoke and other toxic fumes.

**SECTION 11) TOXICOLOGICAL INFORMATION****Skin Corrosion/Irritation**

Causes skin irritation

0000064-17-5 ETHYL ALCOHOL

Contact can irritate the skin. Prolonged or repeated exposure can cause drying and cracking of the skin with peeling, redness and itching.

0000110-54-3 HEXANE

The substance is irritating to the skin

**Carcinogenicity**

No data available.

**Serious Eye Damage/Irritation**

0000067-56-1 METHANOL

Can irritate the eyes and can cause blurred vision and blindness.

**Respiratory/Skin Sensitization**

Material may be an irritant to mucous membranes and respiratory tract.

0000067-56-1 METHANOL

Prolonged or repeated contact can cause a skin rash, dryness, redness and cracking of the skin.

**Germ Cell Mutagenicity**

No data available.

**Reproductive Toxicity**

0000064-17-5 ETHYL ALCOHOL

High concentration may damage the fetus.

0000067-56-1 METHANOL

May be a teratogen in humans since it is a teratogen in animals.

0000110-54-3 HEXANE

Animal tests show that this substance possibly causes toxic effects upon human reproduction.

**Specific Target Organ Toxicity - Single Exposure**

0000064-17-5 ETHYL ALCOHOL

Exposure can cause headache, drowsiness, nausea and vomiting, and unconsciousness. It can also affect concentration and vision.

0000067-56-1 METHANOL

May damage the liver, kidneys and nervous system.

**Specific Target Organ Toxicity - Repeated Exposure**

May cause damage to organs.

Prolonged exposure to inhalation of high concentration can lead to unconsciousness.

0000064-17-5 ETHYL ALCOHOL

Repeated high exposure may affect the liver and the nervous system. Chronic ingestion of ethanol may cause liver cirrhosis.

0000110-54-3 HEXANE

Repeated or prolonged contact with skin may cause dermatitis. The substance may have effects on the central nervous system and peripheral nervous system. This may result in polyneuropathy.

**Aspiration Hazard**

Small amounts of liquid aspirated into the respiratory system during ingestion or vomiting may cause bronchopneumonia or pulmonary oedema.

May be fatal if swallowed and enters airways

0000110-54-3 HEXANE

ASPIRATION causes severe lung irritation, coughing, pulmonary edema; excitement followed by depression.

**Acute Toxicity**

Inhalation of vapour can result in headaches, dizziness and possible nausea.

Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

0000064-17-5 ETHYL ALCOHOL

Inhalation can irritate the nose, throat and lungs.

## 0000067-56-1 METHANOL

Inhalation can irritate the nose, throat and lungs causing coughing, wheezing and/or shortness of breath. Can cause nausea, vomiting, diarrhea and abdominal pain. Exposure to high concentrations can cause headache, dizziness, drowsiness, fatigue, loss of consciousness and death. Methanol is readily absorbed by inhalation, ingestion and dermal exposure and is rapidly distributed to tissues according to the distribution of body water.

## 0000110-54-3 HEXANE

INHALATION causes irritation of respiratory tract, cough, mild depression, cardiac arrhythmias. It has been reported that a 10 minute exposure to 5,000 ppm caused dizziness and a sensation of giddiness INGESTION causes nausea, vomiting, swelling of abdomen, headache, depression.

**Likely Routes of Exposure**

Inhalation, Ingestion, Skin contact, Eye contact

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

## 0000064-17-5 ETHYL ALCOHOL

The substance can be absorbed into the body by inhalation of its vapor or by ingestion.

## 0000106-97-8 BUTANE

The substance can be absorbed into the body by inhalation.

## 0000110-54-3 HEXANE

The substance can be absorbed into the body by inhalation of its vapour and by ingestion.

**Potential Health Effects - Miscellaneous**

## 0000064-17-5 ETHYL ALCOHOL

The following medical conditions may be aggravated by exposure: liver disease. Tests in some laboratory animals indicate this compound may have embryotoxic activity. Tests in animals demonstrate reproductive toxicity. Ingestion may cause any of the following: stupor (central nervous system depression), gastrointestinal irritation. If absorbed through the skin, may be: harmful.

## 0000067-56-1 METHANOL

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: eyes, kidneys, liver, skin. Excessive human exposure to methanol may lead to: fatigue, headache, anaesthetic, neurologic effects, and visual difficulties including blindness or death. Recurrent overexposure may result in liver and kidney injury. Has been toxic to the fetus in laboratory animals at doses that are toxic to the mother. Ingestion may cause any of the following: blindness. Eye contact may cause any of the following: conjunctivitis, mild irritation, corneal opacity.

**SECTION 12) ECOLOGICAL INFORMATION****Toxicity**

## 0000064-17-5 ETHYL ALCOHOL

S gairdneri: 13.0g/l (96hr LC50) Nauplii : 858 g/l (48hr EC50) Ceriodaphnia dubia : 9.6mg/l (10 day NOEC) Freshwater Fish 250mg/l (NOEC) Reference: REACH registration Dossier.

**Persistence and Degradability**

## 0000064-17-5 ETHYL ALCOHOL

Readily biodegradable. Half-life in air = 38 h

## 0000067-56-1 METHANOL

72% aerobic biodegradability.

Readily biodegradable.

## 0000106-97-8 BUTANE

Readily biodegradable.

## 0000110-54-3 HEXANE

Readily biodegradable in water.

**Bio-accumulative Potential**

## 0000064-17-5 ETHYL ALCOHOL

Substance has a low potential for bioaccumulation (log Kow3),

**Mobility in Soil**

## 0000067-56-1 METHANOL

Will not adsorb on soil.

**Other Adverse Effects**



No data available.

### Results of the PBT and vPvB assessment

0000067-56-1 METHANOL

The substance is not PBT / vPvB

0000106-97-8 BUTANE

Readily biodegradable.

This substance is not PBT/vPvB

0000110-54-3 HEXANE

The substance is not PBT / vPvB

## SECTION 13) DISPOSAL CONSIDERATIONS

### Waste Disposal

It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, state and local laws. Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

## SECTION 14) TRANSPORT INFORMATION

### ADG Information

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail".

UN number: 1950

Proper shipping name: AEROSOLS

Hazard class: 2.1

Packaging group: None

### IMDG Information

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea

UN number: 1950

Proper shipping name: AEROSOLS

Hazard class: 2.1

Packaging group: None

### IATA Information

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN number: 1950

Proper shipping name: AEROSOLS

Hazard class: 2.1

Packaging group: None

## SECTION 15) REGULATORY INFORMATION

## HSNO Group Standard: Aerosols Flammable Group Standard 2006: HSR002515

- 2.1.2A Flammable Aerosol
- 6.1E Substances that are acutely toxic – May be harmful, aspiration hazard
- 6.3A Substances that are irritating to the skin

CAS	Chemical Name	% By Weight	Regulation List
0000074-98-6	PROPANE	10% - 30%	DSL,VOC,TSCA
0000106-97-8	BUTANE	10% - 30%	DSL,VOC,TSCA
0000110-54-3	HEXANE	20% - 100%	DSL,VOC,TSCA
0000064-17-5	ETHYL ALCOHOL	1% - 10%	DSL,VOC,IARCCarcinogen,TSCA
0000067-56-1	METHANOL	0% - 1%	DSL,VOC,TSCA

**This material/constituent(s) is covered by the following requirements:**

All the constituents of this material are listed on the *Australian Inventory of Chemical Substances (AICS)*.

## SECTION 16) OTHER INFORMATION INCLUDING INFORMATION ON PREPARATION AND REVISION OF THE SDS

**Glossary**

ACGIH- American Conference of Governmental Industrial Hygienists; ADG- Australian Dangerous Goods Code; CAS- Chemical Abstract Service; DSL- Domestic Substances List; LC- Lethal Concentration; LD- Lethal Dose; OSHA- Occupational Safety and Health Administration; SCBA- Self Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; VOC- Volatile Organic Compounds; WES- Workplace Exposure Standards

**DISCLAIMER**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.