MATERIAL SAFETY DATA SHEET (MSDS)

XCELL Hydraulic Jack Fluid

XHJF

Proper Shipping Name	Xcell Hydraulic Jack Fluid	Hazard Class	n/a
Recommended use	Hydraulic Jack Fluid	Packing Group n/a	
Company	Xcell Products NZ	UN No n/a	
Address	71 Adams drive, Auckland.	Hazchem Code	n/a
	New Zealand	Subsidiary Risk	n/a
Telephone	+64 9 238 2389 (8.00 - 4.30 Mon to Fri)	Poisons Schedule n/a	
Fax	+64 9 238 2399		

Emergency Telephone

+64 21 930 795 (24 hours emergency only)

National Poison Centre (24 hours): 0800 POISON [764 766]

Ingredients	Content*	CAS No
Non Hazardous Ingredients	100%	n/a

^{*}Content: High >60%, Medium 10 to 60%, Low 1 to 10%, Very Low <1%

Physical and chemical properties					
Appearance	Clear Amber Liquid	Solubility	Not soluble		
Physical State	Liquid	% Volatiles	None		
Odour	Mild	Vapour Pressure	< 0.1 kPa		
Specific Gravity	0.85 - 0.89 @ 15°C	Vapour Density	> 2 (Air = 1)		
рН	Not relevant	Flash Point	>140°C (PMCC)		
Boiling Point	>300°C	Flammable Limits	Approximately 1.5% Lower		
			Approximately 6.0% Upper		



Hazard identification

NON-HAZARDOUS SUBSTANCE.

NON-DANGEROUS GOODS.

DANGER:

- May be harmful if swallowed.
- May causes eye irritation. May cause mild skin irritation.

PREVENTION:

Read label before use Keep out of reach of children Wash hands thoroughly after handling When exposure is likely wear protective equipment to prevent skin and eye contamination and inhalation of vapours.

First-aid measures

Eyes: Immediately irrigate with copious quantities of water for at least 15 minutes. Eye lids to be held

open. In all cases of eye contamination it is a sensible precaution to seek medical assistance.

Skin: Wash contaminated skin with plenty of soap and water. Remove contaminated clothing and

wash before reuse. If irritation occurs seek medical advice.

Ingestion: Do Not induce vomiting because of risk of aspiration. Give water to drink. Should vomiting

occur, hold victim with head below hips and seek medical assistance.

Inhalation: Remove victim from exposure - avoid becoming a casualty. Allow patient to assume most

comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if

effects persist.

NOTES TO PHYSICIAN: Treat symptomatically

FOR FURTHER INFORMATION CONTACT (24 hours) THE NATIONAL POISON CENTRE: 0800 POISON (764 766)

Fire-fighting measures

Flash Point: > 14N°C

Auto ignition temperature: Not available Flammable limits in Air % by Not available

Volume:

Product will burn if involved in a fire **Extinguishing media:**

Use foam, CO² or Dry Chemical or Foam to extinguish fire Fire fighting instructions:

Fire Fighters to wear self-contained breathing apparatus if risk to exposure to Protection:

> products of decomposition. Combustion may include: a complex mixture of airborne solid and liquid particulates and gases, including carbon monoxide, acrid smoke,

oxides of sulphur, unidentified organic and inorganic companyonds and carbon manner

dinxide

Unusual fire and explosion

hazards:

Not available

Issue/Revision Date: 02-09-2016 Version: Msds Xhif Xcell Hydraulic Jack Fluid

Page | 2 of 4 Xcell Products N7

Accidental release measures

If product is released or spilled: Contain and prevent contamination of drains and waterways. Use absorbent (soil, sand, sawdust, inert material, vermiculite) Collect into suitable containers for disposal. Dispose through licensed disposal company.

Handling and storage

Handling Not classified as Dangerous Goods. Slippery when split. Avoid accidents, clean up

immediately. Wear protective equipment to prevent skin and eye contamination and

inhalation of vapours.

Storage Observe standard safety precautions and good work practices. Store out of direct

sunlight in a cool place and away from oxidising agents and combustible materials.

Exposure controls and personal protection

Engineering Controls: Maintain concentration below recommended exposure limit. Normal room ventilation is

considered adequate. If risk of over exposure exists ventilation should be provided,

Respirator is not normally required.

Eye / Face Protection: Avoid contact with the skin and eyes, and avoid breathing vapours and mists. When

exposure is likely, use personal protective equipment in a combination appropriate to

the exposure.

If risk of exposure, wear overalls, safety glasses and impervious gloves. **Body Protection:**

Respiratory Protection: Not normally required.

No Data **Exposure Limits:**

Stability and reactivity

Stability of the substance: Stable under normal conditions of use.

Conditions contributing to

instability:

Incompatibility: Strong oxidising agents.

Hazardous decomposition

products:

Conditions contributing to

hazardous polymerization:

Will not occur.



Toxicological information

This product is considered to be non hazardous and non toxic when used in accordance with good industrial hygiene and manufacturers recommendations.

Inhalation: Not normally a hazard due to the non-volatile nature of the product. Inhalation of oil

mist may cause irritation to the upper respiratory system.

Ingestion: Not normally considered to be harmful if swallowed. Swallowing may cause slight

stomach irritation and discomfort.

Skin: Will have a defatting effect on the skin. May cause skin irritation.

Eyes: May cause mild eye irritation.

Chronic Effects: Repeated or prolonged skin contact may lead to irritant and in severe cases, contact

dermatitis.

Ecological information

Prevent product from entering drains, watercourses and sewers.

Disposal considerations

Dispose through licensed disposal company

Regulatory information

HSNO Approval No:

Group Standard:

HSNO Classes:

Poisons Schedule: Not Scheduled Packing and Labelling: Not Regulated

Other information

New Zealand National Poison Information Centre (24 hours): 0800 POISON [764 766] New Zealand Emergency Services: 111

For General Information Xcell Products NZ

Contact: Phone: +64 9 238 2389 [8.00 am to 4.30pm - Mon to Fri]

Fax: +64 9 238 2399

DISCLAIMER: Xcell Products NZ has taken care in compiling this information which is based on sources believed to be accurate. However, Xcell Products NZ assumes no responsibility for the accuracy, completeness or suitability of this information. No liability is accepted directly or indirectly from the use of this information and/or product. End users of the information and/or product are obliged to conform to relevant Local Government regulations and must use their independent judgement in determining its appropriateness for a particular purpose.

lssue/Revision Date: 02-09-2016 Version: Msds Xhjf Xcell Hydraulic Jack Fluid